WHITE LACQUERED ACCESS PANEL SQUARE LOCK

- **Galvanised sheet steel, white coating (RAL 9016)**
- **Panel with strengthened square lock**
- **Detachable panel, left and right flush fit**
- **Secured by wall anchor points**

SEMIN ACCESSORIES

SIZES AND REFERENCES

DIMENSIONS IN MM	INSIDE DIMENSIONS LENGTH x WIDTH	WEIGHT IN KG	REFERENCE	PACKAGING
200 x 200	180 x 160	0.6	A05131	Carton of 10
300 x 300	275 x 295	1	A04962	Carton of 10
400 x 400	375 x 395	1.7	A04963	Carton of 10
500 x 500	460 x 470	2.7	A05130	Carton of 6
600 x 600	560 x 570	3.5	A04325	Carton of 6

PARTICULARITIES OF APPLICATION

- Fit to wall or ceiling (do not walk on it).
- Ceiling installation up to a dimension of 600 x 600 mm.
- Suitable for use in wet rooms.

QUALITY ASSURANCE

Production quality control is integrated into the manufacturing process of each item.

MATERIALS

Parts of the frame	Sheet steel, galvanised Sendzimir DX51D+Z275MA
Panel	Sheet steel, galvanised Sendzimir DX51D+Z275MA
Wall fixing	Sheet steel, galvanised Sendzimir DX51D+Z275MA
Spring hinge	Sheet steel, quality spring Stainless Steel 4310

MANUFACTURE

Spot welded, riveted and powder coating.

QUALITY CONTROL SYSTEM

Visual inspection: Function, purity, complete condition, damage.