



# SEMIN

## REBOUCHEUR LISSEUR

### MULTI-PURPOSE FILLER - INTERIOR

#### TECHNICAL DEFINITION

Multi-purpose filler for interior use.

- Filling holes, cracks, chases.
- Fixing and stick.
- Pasting polystyrene, roses, cornices.
- Finishing.

#### COMPOSITION AND APPEARANCE

Powder filler composed of plaster, calcium carbonate, resin, cellulose fibre and various additives.

Produces a white paste.

#### ACCEPTED SUBSTRATES

All types of interior substrates: plaster, plasterboards, plaster blocks, concrete, cement rendering, concrete blocks, aerated concrete, brick, earthenware, etc...

#### COVERING

Once completely dry, SEMIN REBOUCHEUR can be covered with any type of paint, plaster-based filler, paste-like filler and wallpaper paste.

For tiling, choose an adhesive suited to plaster substrates.

#### REFERENCE DOCUMENTS

- Complies with standard NFT 30 608.
- DTU 59.1: paintwork.

#### TECHNICAL CHARACTERISTICS

- Grain size: fine.
- Adhesion: complies with standard NFT 30 608.
- pH: neutral.
- Setting starts after 50 minutes.
- Setting ends in 1 hr 10 min.
- Bending: 3 N/mm<sup>2</sup>.
- Compression: 7 N/mm.

#### PACKING

1.5 - 5 - 15 - 25 kg bags.  
12 kg pails.

#### STORAGE

9 months in original unopened packing protected from damp for bags, 12 months for pails.

### APPLICATION

#### PRECAUTIONS FOR USE

The temperature during application and drying must be between 8 and 35° C. Do not use on a damp substrate. Do not use once the paste has started to set.

#### PREPARATION OF SURFACES

The substrate must comply with DTU 59.1, i.e. be clean, dry, free of dust and of any trace of stripping oil. Cracks need to be open up.

#### MIXING FACTOR

Use 2.5-3 litres of water for one 5 kg bag (or 12.5 -15 litres for one 25 kg bag) depending on the type of job.

For filling, the less water there is in the mixture, the less the filler shrinks.

#### APPLICATION

Apply with a filler knife.

#### APPLICATION THICKNESS

Up to 2 cm in one coat.

#### CONSUMPTION

1-1.2 kg/m<sup>2</sup>/mm thickness.

#### DRYING TIME

This depends on the weather conditions, on the type of substrate and on the applied thickness.

As a general rule, for 1cm thickness, SEMIN REBOUCHEUR dries in 6 hours.

## MULTI-PURPOSE FILLER

The SEMIN REBOUCHEUR LISSEUR multi-purpose filler can be used for many interior jobs: filling, bedding, fixing or pasting slabs and polystyrene cornices and mouldings.

### ADVANTAGES

- Excellent adhesion to most substrates.
- Very smooth for a high-quality finish.

### APPLICATION TIP

To achieve long-lasting results, open up, clean and bevel cracks before applying SEMIN REBOUCHEUR LISSEUR.

AFNOR classification NFT 36.005  
Family III - Class 3

