



CUISINE & SALLE DE BAIN

LIGHT FINISHING PLASTER

TECHNICAL DESCRIPTION

Ready-to-use light waterproof paste plaster for finishing walls in damp rooms: kitchen and bathrooms.

Prepare thoroughly before painting or hanging wallpaper.

COMPOSITION AND APPEARANCE

Resin emulsion, calcium carbonate, light filler, waterproof additive and various adjuvants.

The resulting paste is green in colour.

SUITABLE SURFACES

- Plasterboard.
- Plaster tiles.
- Earthenware tiles.
- Concrete.
- Cement rendering.
- Kitchen and bathroom repair and filling plaster.

COATINGS

- Paint.
- Wallpaper.

APPLICATION

PRECAUTIONS FOR USE

The temperature for application and during drying must be between 8 and 35°C.

Do not use on wet surfaces.

PREPARATION OF SURFACES

They must meet DTU 59.1, i.e. clean, dry, free from dust and all traces of moulding oil.

APPLICATION

It is applied using a painter's knife or a plasterer's trowel.

THICKNESS OF APPLICATION

Up to 1 mm in one pass.

COVERAGE

About 150 to 200 g/m².

DRYING TIME

Depends on ambient conditions, nature of the surface and thickness of application.

On average, the plaster is dry in 12 to 24 hours.

TECHNICAL SPECIFICATIONS

- Grain size: Up to 0.2 mm.
- Adhesion: complies with NFT 30 608.
- pH: 8.
- Dry weight: 65%.

PACKING

1 and 5 kg pails.

STORAGE

6 months in the original undamaged packaging protected from frost and heat sources

LIGHT KITCHEN AND BATHROOM FINISHING PLASTER

Special finishing plaster for damp rooms (kitchen and bathroom), before painting or wallpapering.

ADVANTAGES

- Good moisture resistance.
- Easy and quick to use.
- Free from solvent, clean tools in water.

AFNOR Classification NFT 36.005
Family III - Class 2.

