



SEMIN AIRLESS

SPECIAL AIRLESS AND SPRAY COATING

TECHNICAL DEFINITION

SEMIN AIRLESS is an interior finishing coating that can be Airless sprayed. Ideal for preparing floor supports, wall concrete and plaster boards before applying paint finish.

SEMIN AIRLESS provides an even, uniform and regular finish. For a more professional finish, rub down slightly once dry, with a fine grain.

COMPOSITION AND APPEARANCE

Acrylic emulsion resin, mineral content, cellulose derivatives, preservation agent and other additives.

The resulting paste is white and its consistency is adapted to its airless application.

ACCEPTED SUBSTRATES

- Plaster boards.
- Smooth concretes.
- Coverage coatings.
- Plaster tiles.
- Old paintwork.

LAYERS

The SEMIN AIRLESS can be applied using an acrylic or gloss paint.

REFERENCE DOCUMENTS

DTU 59.1.

TECHNICAL CHARACTERISTICS

- Dry extract: 72 %.
- Density: 1.8
- VOC: 0.63 g/litre.

ASSOCIATED PRODUCTS

SEMIN UNDERLAYER as an underlayer for plaster boards.

PACKING

25 kg plastic bags and pails.

STORAGE

18 months away from frost, in original unopened packaging.

APPLICATION

PRECAUTIONS DURING USE

The application and drying temperature must be between 8 and 35° C. Do not apply to frozen surfaces.

SURFACE PREPARATION.

Surfaces must conform to DTU 59.1 i.e. they must be clean, hard, without traces of any paring agent...

Plaster boards must have a primer coat.

APPLICATION.

SEMIN AIRLESS can be sprayed with all kinds of 695, 795 type or Mark 5 Airless machines, with avec plunger or airless silo. Nozzles 527 to 531. Spray at about

80 cm from the relevant surface.

DRYING TIME.

6 to 24 hours depending on the amount applied.

QUANTITY.

Variable according to amount applied, 600 g to 1 kg/m².

INTERIOR AIRLESS FINISH COATING

Specially developed for Airless application, SEMIN AIRLESS offers very careful performance before applying paint, while saving considerable time thanks to its mechanical application.

ADVANTAGES

- Odourless.
- Tools can be cleaned with water.
- Easy to rub down.

APPLICATION TIP

The spray gun can be replaced with a black 60 filter mesh on the pump.

