



DALLE SYSTEM

MULTI-BINDER JOINT FILLER FOR FLAGSTONE PAVEMENT

DALLE SYSTEM is composed of several high performance synthetic binders, a hydraulic binder and very high quality minerals. Specially designed for paving stone jointing, this innovative product with outstanding mechanical properties has the advantage of being very easy to implement.

APPLICATION FIELDS.

Outdoor laying in private property: lanes, garage entrances, terraces, etc.

Urban spaces – pavements, squares, pedestrian areas, car parks, etc.

By stabilising the paving stones, the multi-binder joint filler provides a long-lasting effect, ensuring the flatness of the pavement, particularly on driveways.

It also provides a considerable weed-control effect. Thanks to the broad range of colours available, it can be matched with the colour of most paving stones on the market.

PACKING.

- 56 bags, each 16 kg on EURO-pallet.
- Protection: plastic-wrapped.

APPLICATION

APPLICATION.

- Lay a 2-3 cm thick bedding layer with 0/2 - 0/4 mm sand.
- Lay the PAVING STONES on the bedding layer, maintaining the maximum and minimum thickness of the joints.
- Spread Pavement System over the joints and fill them evenly using a broom.
- Compact the surface with a rubber-protected tamper or hammer.
- Add more Pavement System until the joints are saturated.
- Make sure that the paved surface is perfectly clean so that PAVEMENT SYSTEM does not leave any marks when wet (these marks do disappear with time).
- Drizzle water over the whole jointed area.
- Drizzle again 2 or 3 times at 10-15 min. interval to make sure that PAVEMENT SYSTEM is wet down to the bottom of the paving stones.

Pavement System will set within 24-48 hours depending on the weather conditions.

PRECAUTIONS FOR USE.

- The pavement must be laid according to professional standards and the surface must be dry.

- Pavement System can only be used on top of a calibrated drainage bedding layer: 0/6 sand, 0/2 – 0/4 crushed or vitrified gravel.
- Joint length must be between 5 and 10 mm.
- Do not use when temperatures are below 10°C or in the rain,
- The manufacturer's liability is limited to replacing the product.
- For subsequent maintenance, avoid using pressurised jet washers.

USE.

One sack of MULTI-BIND can treat a surface area of 10m² depending on joint thickness and paving stone format.

The Multi-binder joint filler has a density of 1.9 g/cm³, according to the density of the compacting process.

PRECAUTIONS FOR USE.

Keep out of the reach and sight of children
Product labelled as hazardous. Contains cement: gloves should be worn. Refer to the safety label on the packaging. Observe the precautions for use and the safety advice. Safety data sheet available at www.quickfds.com, read before use.

MULTI-BINDER JOINT FILLER FOR FLAGSTONE PAVEMENT

DALLE SYSTEM is composed of several high-performance synthetic binders, a hydraulic binder and high-quality minerals.

Specially designed for pavement jointing, this innovative product with outstanding mechanical properties has the advantage of being very easy to implement.

ADVANTAGES

- Stabilises paving stones and adapts to ground movement.
- Ensures pavement permeability.
- High resistance to changing weather conditions
- Provides a weed-control effect.

APPLICATION TIP

Make sure that PAVEMENT SYSTEM goes all the way to the bottom of the paving stones by compacting the surface carefully, and repeating the process 2 or 3 times.

