



IMPERMEABILISANT PROTECTEUR ANTI-TACHE

ANTI-STAIN PRODUCT FOR STONES, PAVING BLOCKS AND FLAGSTONES

TECHNICAL DEFINITION.

Damp-proofing agent for terracotta tiles and paving blocks, natural stone, reconstituted stone, marble, limestone, opus and stoneware.

Protects against virtually all kinds of stains—oil, wine, coffee, etc.

Ideally used for interior and exterior paving blocks. Does not alter the initial appearance of the material treated.

Referred to as an oil-repellent, this agent protects the surface against motor oil and grease.

APPEARANCE.

Liquid form.

ACCEPTED SUBSTRATES.

- Paving blocks.
- Terracotta.
- Reconstituted stone.
- Limestone.
- Stoneware.
- Tiles.
- Natural stone.
- Marble.
- Opus.
- Etc.

APPLICATION

PRECAUTIONS FOR USE.

The temperature during application and drying must be between 6 and 30°C.

Do not apply onto windows and glass panes. Check colour-fastness before applying onto glazed surfaces.

APPLICATION.

The product is ready to use. Do not apply onto a wet surface or under the rain.

First clean the paving blocks, flagstones or stones with a degreaser to restore the original, clean surface. Rinse and allow to dry.

Once completely dry, apply liberal amounts of the product with a paintbrush, roller or spray.

Allow to dry for 4 to 6 hours in ideal weather conditions (between 6 and 30°C) before proceeding with a second application.

The surface can be walked on 3 hours later. The product becomes fully effective after 24 hours. Clean tools with clean water.

CONSUMPTION.

Around 250 g/m².

PACKING.

2, 5 and 10 litre cans.

STORAGE.

12 months in unopened original packing protected from frost and high heat.

ANTI-STAIN PRODUCT

Protects all porous surfaces.

Damp-proofing agent and oil-repellent.

ADVANTAGES

- Ready to use.
- Damp-proofing agent and oil-repellent.
- Invisible: non-wet appearance.

