

# BARBECUE KIT

## WHITE GROUT & ANTI-STAIN PRODUCT



**TILE GROUT  
WHITE**  
HIGH TEMPERATURE  
For 25 m of brick

**ANTI-STAIN  
PRODUCT**  
FOR HARD-TO-  
REMOVE OIL STAINS  
Covers around 10 m<sup>2</sup>

**INCLUDED**

1 spray  
1 serrated spatula  
2 latex gloves  
1 jointer

### WHITE TILE GROUT HIGH TEMPERATURE

**DIRECTIONS FOR USE.** Prepare a small amount of grout at a time (1 kg of powder for 0.5 litre of water), the working time being limited to 30 mins. Apply the grout onto the surface, either by laying 3 cm-diameter pads or by spreading with the serrated spatula. Position the element to set and press to adjust in place. Waiting time before first barbecue use: 48 hours. Please note: do not grout inside the barbecue hearth (as the joint will blacken and crumble in time).

**CONSUMPTION.** 200 g/m<sup>2</sup>, i.e. 25 m of brick with the 5 kg of product.

**DRYING TIME.** Depends on ambient conditions and on the substrate. In general, the product dries in 6 hours.

#### TECHNICAL DEFINITION.

White tile grout in fine powder form for barbecue elements.

**COMPOSITION.** Aluminous cement (for resistance to high temperature), filler, resin and various additives.

**ACCEPTED SUBSTRATES.** Cement, concrete, brick, stone, reconstituted stone, terracotta, cellular concrete, old paintwork, old tiling.

**MIXING FACTOR.** 50 % (0.5 litre of water for 1 kg of powder, or 2.5 litres of water for 5 kg of powder).

**WORKING TIME.** Around 30 mins.

**PREPARATION OF SURFACES.** The surfaces must be clean, dry, free of dust and any trace of oil.

**PRECAUTIONS FOR USE.** The temperature during application and drying must be between 5 and 35°C. Contains cement, classified as an irritant. It is strongly recommended to wear working clothes and gloves to avoid prolonged contact with the skin. Protect from the rain for 24 hrs.

**STORAGE.** 12 months in unopened original packing protected from frost and high heat. In case of ingestion, immediately refer to a general practitioner and show him the label.

### ANTI-STAIN PRODUCT FOR HARD-TO-REMOVE OIL STAINS

#### DIRECTIONS FOR USE.

Clean the barbecue elements with a degreaser to restore the original, clean surface. Rinse and allow to dry.

Once completely dry, apply liberal amounts of the product with a paintbrush, roller or spray. For best results, up to three applications may be needed, or until the material gets saturated.

Allow to dry for 4 to 6 hours in ideal weather conditions (between 6 and 30°C) before proceeding with the subsequent applications.

Clean tools with clean water.

**IMPORTANT:** Do not apply onto a wet surface or under the rain.

#### TECHNICAL DEFINITION.

Damp-proofing agent for terracotta tiles and paving blocks, flagstones, natural stone, reconstituted stone, marble, limestone, opus and stoneware.

Protects against virtually all kinds of stains—oil, wine, coffee, etc.

Referred to as an oil-repellent, this agent protects the surface against motor oil and grease.

#### PRECAUTIONS FOR USE.

Keep out of children's reach. Keep the container with its lid on, in a cool and well-ventilated area.

Do not eat, drink or smoke while using the product. Avoid contact with the eyes and the skin. In case of contact with the eyes, rinse immediately and thoroughly with water, and refer to an eye specialist. After contact with the skin, wash your hands with soapy water. In case of ingestion, immediately refer to a general practitioner and show him the label.

The product is not classified as dangerous by the present-day legislation.

## BARBECUE KIT

### Contains:

- 5 kg sack of white tile grout.
- 2 litres of anti-stain product.
- 1 spray.
- 2 latex gloves.
- 1 jointer.
- 1 serrated spatula.

### ADVANTAGES

#### WHITE TILE GROUT:

- Strong adhesion to all substrates.
- Quick setting.
- Does not shrink.

#### ANTI-STAIN PRODUCT:

- For hard-to-remove oil stains.

