



CE 78 PERFECT'LISS

LIGHTWEIGHT FINISHING COMPOUND FOR INTERIOR SURFACES

TECHNICAL DEFINITION.

CE 78 PERFECT'LISS is a ready-mix lightweight paste compound specially formulated for finishing interior surfaces (walls and ceilings).

COMPOSITION AND ASPECT.

Resin, water, calcium carbonate, lightweight fillers, preservation agent and various adjuvants.

The paste is white.

SUITABLE SUBSTRATES.

- Plaster board.
- Plaster block.
- Plaster.
- Concrete.
- Aerated concrete.
- Cement coating.
- Brick.
- Old paintwork.
- Fibreglass.

COVERINGS.

- Wall covering.
- Paint.

REFERENCE DOCUMENTS.

- DTU 59.1
- NF 30.608
- DoP.

PACKAGINGS.

17 kg buckets on covered pallet.

STORAGE.

18 months in original unopened packaging away from frost and high temperatures.

APPLICATION

PRECAUTIONS FOR USE.

The temperature on application and during drying must be between 8 and 35° C. Do not apply on a wet substrate. Do not use on a frozen substrate.

PREPARATION OF SUBSTRATES.

The substrates must comply with the DTU 59.1 standard i.e. be dry, clean, hard, free of any trace of separating agent, etc.

APPLICATION.

The product can be applied with a roller, a spatula. For application with a roller, stir the product before use.

CONSUMPTION.

Variable depending on the thickness applied: 0.4 to 2 kg/m²

DRYING TIME.

A repeat coat can be made 6 to 24 hours after application of the first coat, depending on the ambient conditions.

TECHNICAL SPECIFICATIONS.

- Thickness of application: 5 mm maximum.
- Density: 1.3 (1.8 for a traditional filler).
- Reaction to fire: A2s1 d0.

LIGHTWEIGHT READY-MIX PASTE

CE 78 PERFECT'LISS is especially formulated to combine the benefits of a product with excellent filling capacities with those of a smoothing filler.

ADVANTAGES

- High-build power.
- High degree of whiteness, very good covering power.
- Manual or mechanical application.
- Slides very well.
- Easy sanding.

