



WHITE DECO MOISTURE-RESISTANT ACCESS PANEL



- Aluminium profile frame secured by «Tox» connections
- Lip seal along the whole circumference
- Safety catch on both sides
- Hidden latches
- No jointing of the cover
- For wall and ceiling installation
- White impregnated GKBI plaster, H2 quality
- Ready to paint

SIZES AND REFERENCES - PRODUCTS IN STOCK

DIMENSIONS IN MM	INSIDE DIMENSIONS LENGTH x WIDTH	OUTSIDE DIMENSIONS LENGTH x WIDTH	WEIGHT IN KG	GENCOD	REFERENCE
200 x 200	158 x 190	240 x 240	0,8	-	A07142
300 x 300	258 x 290	340 x 340	1,4	-	A07298
400 x 400	358 x 390	440 x 440	2,2	-	A06759
500 x 500	458 x 490	540 x 540	3,2	-	A07144
600 x 600	558 x 590	640 x 640	4,4	-	A07299

Other special dimensions available to order, see page 29.

PARTICULARITIES OF APPLICATION

- Fit to wall or ceiling (do not walk on it).
- Suitable for use in wet rooms.
- If wall-fitted, upwards closing.
- Reliability of the opening system.
- Can be tiled.
- Dust-tight

Individual protective box, installation instructions on the back of the box.

QUALITY ASSURANCE

Production quality control is integrated into the manufacturing process at each stage of production, assembly and packaging. The raw materials and external components undergo the quality control system on arrival of the goods.

MATERIALS

Frame Components	Bar profiles, Eloxale ALMgSi 0.5 F22 quality
Stopping angle, Stopping device, Angle sections, Latch	Sheet steel, galvanised DC 01 Am 1,0 mm
Plaster board	White plaster with impregnated GKBI surface suitable for wet rooms
Latch	Steel/plastic
Seals	EPDM lip seal
Steel nails	Steel

