



# RE-BOUCH-TROU

## FILLER IN AN AEROSOL SPRAY

### TECHNICAL DEFINITION

Filler in an aerosol spray, ideal for filling screw holes and small cracks.

Re-bouch-trou can be used to for precise, high-quality filling without soiling. It is very easy to use with no need for any additional tools.

### COMPOSITION AND ASPECT

Emulsion resin, lightweight filling material and various adjuvants. The resulting paste is snow-white.

### TECHNICAL SPECIFICATION

- Density: 0.4
- pH: 7
- Excellent quality of application.

### SUITABLE SUBSTRATES

Interior walls:

- Plaster.
- Aerated concrete.
- Plaster board.
- Concrete.
- Masonry.
- Cement coating.
- Textured coating.

### PACKAGING

Aerosol containing 125 ml net of product.

### STORAGE

2 years in original unopened packaging stored away from frost and high temperatures.

## APPLICATION

### PRECAUTIONS FOR USE

The temperature on application and during drying must be between 8 and 35° C.

### CAUTION

Container under pressure: may burst under the effect of heat. If a physician is consulted, keep the container or label available. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and any other flammable source. Do not smoke. Discard the content and container in an authorised disposal facility. Keep away from solar rays. Do not expose to a temperature greater than 50° C. Do not puncture or burn, even after use. Do not inhale the aerosols. Do not use for a use other than that for which the product is intended. Intended for use by the general public and professionals.

### PREPARATION OF SUBSTRATES

They must be clean, dust-free and free of any trace of formwork oil.

### APPLICATION

1. Shake the aerosol vigorously upside down for 1 minute
2. Carry out a small spray test to prime the product and judge the pressure to be exerted on the diffuser (on a piece of waste cardboard for example).
3. Insert the spout, head upwards in the hole or crack.
4. Spray until the hole is filled (for cracks, spray from the bottom to the top). Brief sprays will fill holes better.
5. Smooth with the spatula. Shake between spraying.
6. Rinse the spout in hot water.
7. If necessary, apply a second coat on the following day.

Thoroughly clean the tip to reuse the product, limited to 2 days after first use.



## ADVANTAGES

- Quick and easy filling.
- Lightweight product.
- Fast-drying: 4 hours.
- Integrated spatula.
- Matt white finish.

## APPLICATION TIP

Shake vigorously until you hear the balls move around freely inside the aerosol.



SHAKE, SPRAY,  
SMOOTH.

THAT'S IT!

