

SPECIAL CMV
AND NOISY
TECHNICAL
DUCTS

INTEGRATED
INSULATION

METALLIC WHITE PAINTED ACCESS HATCH **HQ**



- Galvanised sheet steel, white coating, RAL 9016
- Opening system: push/release
- Hollow seal for guaranteed air-tightness
- Non-removable panel
- Simple installation, secured by wall anchor points

RT 2012
AIR/DUST TIGHT

SIZES AND REFERENCES - PRODUCTS IN STOCK

DIMENSIONS IN MM	INSIDE DIMENSIONS LENGTH x WIDTH	OUTSIDE DIMENSIONS LENGTH x WIDTH	WEIGHT IN KG	GENCOD	REFERENCE
200 x 200	175 x 195	-	-	3585501090400	A09040
300 x 300	275 x 295	-	-	3585501089985	A08998
400 x 400	375 x 395	-	-	3585501090417	A09041
500 x 500	460 x 470	-	-	3585501090424	A09042
600 x 600	560 x 570	-	-	3585501090325	A09032

DETAILS OF APPLICATION

- Fit to wall or ceiling (do not walk on it).
- Suitable for use in wet rooms.
- Air-tightness tested up to 600 Pa (Class 4).
- Acoustic absorption tested according to DIN EN ISO 10140-2: 2010.

QUALITY ASSURANCE

Production quality control is integrated into the manufacturing process of each item. Raw materials and the external components undergo rigorous control on their arrival in the factory.

MATERIALS

Frame, elements of the frame: Galvanised sheet steel, Sendzimir DX51D+Z275MA

Panel: Galvanised sheet steel, Sendzimir DX51D+Z275MA

Wall anchor points: Galvanised sheet steel, Sendzimir DX51D+Z275MA

Spring hinge: Sheet steel, quality spring.
Stainless steel 4310

Fastener: Steel ST42-2

Insulating material: FEF (Flexible Elastomeric Foam)



USED WITH
A SEMIN
SILICONE

