



SEMIN REBOUCHEUR PRO

INDOOR SURFACE POWDER FILLER

TECHNICAL DEFINITION.

Powder filler for interior use. Cracks, holes and dents of all sizes. It can also be used to seal and secure.

COMPOSITION AND APPEARANCE.

Compound in powder form, composed of plaster, calcium carbonate, mineral filler, cellulose, and various adjuvants.

The resulting paste is white.

SUITABLE SUBSTRATES.

All types of unworked or painted interior substrates: Plaster, plaster boards, plaster bricks, concrete, cement coatings, concrete blocks, aerated concrete, bricks, terracotta, etc.

COATING.

Once completely dry can be covered by all types of paints, plaster-based coatings, textured coatings, wallpaper paste. Tile adhesives must be suitable for plaster substrates.

REFERENCE DOCUMENTS.

- Filler complies with standard NF T30-608.
- DTU 59.1: Paint work.

TECHNICAL PROPERTIES.

- pH: neutral.
- Setting time: 30 minutes depending on the ambient conditions and the thickness applied.
- Adhesion: complies with NF T30-608.

PACKAGING.

5 kg and 15 kg bags on a covered pallet.

STORAGE.

9 months in original, unopened packaging in a dry place.

INSTRUCTIONS FOR USE

PRECAUTIONS FOR USE.

The temperature on application and during drying must be between 8 and 35°C. Do not use on a damp substrate. Do not use paste that has begun to set.

PREPARATION OF SUBSTRATES.

They must comply with DTU 59.1, i.e. be clean, dry, sound, hard, dust-free and free of any trace of formwork oil. Correctly open up cracks.

MIXING PROPORTIONS.

- 2.75 litres of water per 5 kg bag.
- 8.25 litres of water per 15 kg bag.
- 2 volumes of powder for 1 volume of water.

APPLICATION.

Application is with a plaster knife.

CONSUMPTION.

1 kg/m²/mm of thickness.

DRYING TIME.

It depends on the ambient conditions, the type of substrate and the thickness of application. As a general rule, for 1 cm of thickness, SEMIN PLASTER FILLER PRO will dry in 6 hours.

SURFACE FILLER

Surface filler to quickly fill cracks, holes and dents of all sizes without shrinkage or cracking.

ADVANTAGES

- Minimal shrinkage.
- Excellent glide.
- Extra-fine product.
- Easy sanding.
- Setting time: 30 minutes.
- High degree of whiteness.

APPLICATION TIPS

For a perfect hold, open, clean and bevel the cracks before applying the filler.

AFNOR classification NFT 36.005
Family III - Class 3.

FDES Environmental and Health Declaration Sheets available on the site

www.inies.fr

