



SEMIN ENDUIT 2 EN 1

SEMIN 2 IN 1 FILLER

MULTI-FUNCTION FILLER - FINISHING COAT SMOOTHING

TECHNICAL DEFINITION.

Ready-to-use paste specially formulated for jointing mitred-edge plasterboards in association with plaster tape.

The compound is already mixed: it is suitable for bonding and finishing joints.

COMPOSITION AND ASPECT.

Resin, water, calcium carbonate, preservation agent and various adjuvants. The paste is white.

SUITABLE SUBSTRATES.

All types of plaster board with or without insulation (glass wool, rock wool, polystyrene) with mitred edges and carded surfaces.

COVERINGS.

- Plaster board primer.
- Plaster-based finish coating.
- Wallpapers, paints, wall coverings.

TECHNICAL SPECIFICATIONS.

Cracking: no cracks up to 5 mm thick.

PACKAGING.

5 kg pot.

STORAGE.

9 months in original unopened packaging away from frost and high temperatures. Keep out of reach of children. In the event of swallowing, immediately consult a doctor and show him the packaging.

APPLICATION

PREPARATION OF SUBSTRATES.

Cut boards must be bevelled and dusted.

APPLICATION.

Before actual jointing, fill any accidental gaps between boards and any other areas (spalls, deterioration of the surface etc.). Apply manually by «buttering» the mitred-edge using a 10 or 15 cm plaster spatula and then adding the tape (milled face against the jointing coating).

Then add a finishing coat, allow to dry and finish to hide the tape. Also hide the screw heads.

Apply a tape band on the inside ceiling edges ensuring that the concrete is free of any trace of formwork oil.

For projecting vertical edges, use reinforced tape (reinforcing face on board side) or a metal square edge strip.

ASSOCIATED TAPES.

All types of paper tapes.

COVERAGE.

Around 500 g/m² of board.

DRYING TIME.

A repeat coat can be made 24 hours after the first application.

PRECAUTIONS FOR USE.

The temperature on application and during drying must be between 5° and 30°C.

Do not use on a damp substrate. Do not use on a frozen substrate.

1 PRODUCT: 2 FUNCTIONS

Bonding and finishing
of the tape.

Coating and smoothing
of plaster boards.

ADVANTAGES

- Ready-to-use.
- Excellent finish quality.
- Versatile.

APPLICATION TIP

To save time, remember
to prepare in advance
the jointing tapes cut
to the right length.

