



PLATRE EXPRESS

EXPRESS PLASTER FILLING AND SEALING

TECHNICAL DEFINITION.

Traditional plaster for sealing, filling and modelling as well as for small coating work on interior walls and ceilings. Its fast setting time makes it particularly useful for small projects or when a short waiting time is required.

Express Plaster can be used for:

- Brickwork: Installing distribution partitions in bricks or cinder blocks.
- Coating: Coating small surfaces.
- Sealing: Sealing of ducts or electrical outlets, junction boxes.

- Filling: Holes and cracks.

- Modelling: Moulding of small or large parts.

REFERENCE DOCUMENTS.

DTU 25.1

PACKAGING.

25 kg bags on a wrapped pallet.

STORAGE.

6 months in original, unopened packaging in a dry place.

INSTRUCTIONS FOR USE

PRECAUTIONS FOR USE.

The temperature on application and during drying must be between +8°C and 35°C.

Do not use paste that has begun to set.

Dampen the substrate before application.

USE.

Approximately 15 minutes.

MIXING RATIO.

To be adapted according to the work.

From 15 to 25 litres of water per bag.

APPLICATION.

Manual. Maximum thickness: 10 to 25 mm.

TIME BEFORE SECOND COAT.

Brickwork, sealing: As soon as the plaster sets.

Coating: 1 to 4 weeks.

EXPRESS PLASTER

Traditional plaster for sealing, filling and modelling as well as for interior plastering work.

ADVANTAGES

- Fast setting time.

APPLICATION TIPS

Wet the substrates thoroughly before application and work using successive small quantities.

