



PLATRE POLYVALENT

MULTI-PURPOSE PLASTER

COAT - FILL BRICKWORK - SEAL

TECHNICAL DEFINITION.

Multifunctional manual plaster suitable for a large number of interior building works: plastering, plumbing, electricity, joinery, etc.

Its extreme smoothness and its gradual setting make it easy to use.

Multi-purpose Plaster can be used for:

- Brickwork: Installing distribution partitions in bricks or cinder blocks.
- Coating: Setting time suitable for traditional coating of small or medium-sized surfaces.

- Sealing: sealing of ducts or electrical outlets, junction boxes.
- Filling: Holes and cracks.
- Modelling: Moulding of small or large parts.

REFERENCE DOCUMENTS.

DTU 25.1

PACKAGING.

25 kg bags on a wrapped pallet.

STORAGE.

6 months in original unopened packaging in a dry place

INSTRUCTIONS FOR USE

PRECAUTIONS FOR USE.

COATING: After mixing the plaster, apply it to the substrate then float as soon as the plaster thickens.

Work the plaster to obtain a good flatness.

Tighten and skim. Smooth.

BRICKWORK: After mixing the plaster. Use the plaster to lubricate the bricks. Install the offset bricks. Cut the plaster with a knife once it has stiffened.

MIXING RATIO.

To be adapted according to the work:

- Coating: Around 25 litres of water per bag.
- Brickwork: Around 20 litres of water per bag.

APPLICATION.

Manual.

CONSUMPTION.

COATING: Approximately 8 kg/m².

BRICKWORK: Approximately 5 kg/m².

TECHNICAL PROPERTIES.

- Working time: Approximately 50 minutes.
- Maximum thickness: 15 mm.

TIME BEFORE SECOND COAT.

- Brickwork: 24 hours.
- Coating: 2 to 6 weeks.

MULTI-PURPOSE PLASTER

Multifunctional manual plaster suitable for a large number of interior building works.

ADVANTAGES

- Excellent stiffening of partitions.
- Excellent finish.
- Extremely smooth finish.

