



SOUS-COUCHE

PLASTERBOARD PRIMER

TECHNICAL DEFINITION

This general-purpose undercoat is suitable for indoor use to obtain a substrate ready to receive paint, wallpaper, wall coverings and every type of filler.

Allows subsequent removal of wallpaper or wall coverings without damage to the substrate.

Specially formulated for application to plasterboard.

COMPOSITION AND APPEARANCE

Emulsion resin, calcium carbonate, rheological agent and various additives.

The resulting paste is white and has a liquid consistency.

ACCEPTED SUBSTRATES

Indoor walls and ceilings:

- Plasterboard.
- Fibro-cement panels.
- Old stripped surfaces.
- Brick.
- Old painted surfaces.
- Plaster blocks.
- Concrete raw from formwork release.

COVERING

- Wallpaper.
- Paint.
- Wall coverings.
- All types of render.

DOCUMENTS TO CONSULT DTU 59.1

Note that DTU 59.1 requires the priming of certain substrates, in particular plasterboard.

TECHNICAL CHARACTERISTICS

- Density: 1.5.
- Dry Matter: 64.7 %.
- pH: 7.

PACKAGING

25 kg pails.

STORAGE

6 months in unopened original packing protected from cold and extreme heat.

APPLICATION

PRECAUTIONS FOR USE

Do not apply when the temperature is less than 5°C.

For renovation, make sure that the primer does not soak through the previous covering.

PREPARATION OF SURFACES BEFORE APPLICATION

Indoor substrates must be in conformity with DTU 59.1, i.e., be clean, dry, hard, free of dust and any trace of release agent.

Wash and rinse old paint.

APPLICATION

It is possible to add up to 5% water.

To be applied in a single coat using a roller, brush or gun. Clean tools in water.

DRYING TIME

Approximately 3 to 4 hours depending on the substrates and the ambient condition.

Before applying wall coverings, wallpaper or painting, make sure that the PRIM-PLAQUE is absolutely dry.

CONSUMPTION

Approximately 200 g/m².

UNDERCOAT FOR PLASTERBOARD

The use of PRIM-PLAQUE before painting or applying wall coverings is a way of optimizing the quality of the substrate and avoiding damage to it when the coverings are subsequently removed.

ADVANTAGES

- High opacifying ability.
- Substantial saving on the number of coats of paint.

APPLICATION TIP

To eliminate risk of peeling or blistering always apply Prim-Plaque to a totally dry and dust-free substrate.

