



1 PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Ruban adhésif universel pour la jonction des lés.

Trade name	Product name	Universal adhesive tape
Product dimensions	Height (in mm)	170
	Width (in mm)	60
	Length (in mm)	170
	Length (in m)	40
	Weight (in kg)	0.25
	Thickness without protection (in mm)	0.28
Material	Solvent-free acrylate dispersion	
Consumption	Average consumption (per m ²)	2.4
	Average consumption (per m)	1
Install information : all products	Unit pack : type	carton
	Unit pack : height (in cm)	14
	Unit pack : width (in cm)	39
	Unit pack : depth (in cm)	39
	Unit pack : weight (in kg)	8
	Number of products / parcels (in items)	8
The product	Adhesion	35N/25mm
	Temperature range	-40°C +100°C

2 ADVANTAGES

- Very good ageing test.
- Peelable protection: Yellow siliconed kraft paper.

3 AREA OF APPLICATION

- Seals and affixing of vapour barrier protective film.
- Insulating joint for glass wool, rock wool, aluminium insulation, hemp and flax

4 REFERENCES TO TECHNICAL DOCUMENTS


- Customs nomenclature: 39191080
- DIN EN 1939

5 CONDITIONS FOR USE

- Application in temperatures >-10°C

6 INSTRUCTIONS FOR USE

Air-tightness is provided by affixing universal adhesive tap over the overlap. The vapour protection strips must be sufficiently taught without any folds to ensure uniform application of the adhesive tape



7 REFERENCES & PACKAGINGS

- Product reference : A04083
- Barcode : 3585501040832
- Packaging : 8 rolls per carton.
48 cartons per pallet.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Vapour barrier: use with universal tape.