



SPECIAL VAPOUR BARRIER ADHESIVE

TECHNICAL DEFINITION.

SPECIAL VAPOUR BARRIER ADHESIVE is intended for vapour barrier sealing.

Seals the edges of the airtight membrane (SEMIN VAPOUR BARRIER).

Excellent adhesion on most materials without using primer.

COMPOSITION AND APPEARANCE.

- Acrylate copolymer base.
- Solvent-free and isocyanate-free.
- Blue/green.

TECHNICAL FEATURES.

- Retains elasticity.
- Dry extract 73 %.
- Density: 1.08kg/L.
- Temperature resistance: -10°C to +50°C.
- Very good moisture resistance.
- Frost resistant up to -10°C.

PERMISSIBLE SUBSTRATES.

Concrete, plaster, stone, sealant, wood, metal.

SAFETY.

A safety data sheet is available at www.quickfds.com. It should be read before use.

Keep out of reach of children.

If swallowed, seek medical advice immediately and show the doctor the packaging or label.

Wearing gloves is recommended.

PACKAGING.

310 ml.

STORAGE.

24 months in original unopened packaging away from frost and high temperatures.

INSTRUCTIONS FOR USE

PRECAUTIONS FOR USE.

The temperature on application must be between +5 and +40°C.

Do not apply when relative humidity >70 %.

Do not apply to damp substrates.

PREPARATION OF SUBSTRATES.

They must be clean, dry, cohesive, safe, dust-free and free of any trace of formwork oil.

TYPE OF APPLICATION.

The adhesive is applied to all edges of the vertical and horizontal walls including the wall/floor junction.

Apply a continuous 6-8 mm bead of adhesive and install the vapour barrier as quickly as possible (max. 15 min) by pressing lightly.

This adhesive combines the benefits of double-sided and reactive adhesives.

Clean tools with clean water before polymerization.

DRYING TIME.

Usually 1-3 days.

Drying may take longer depending on the quantity applied, the temperature and moisture levels.

SPECIAL VAPOUR BARRIER ADHESIVE

For sticking and sealing difficult areas on all substrates.

ADVANTAGES

- Solvent free.
- Application on all materials.
- High tack.
- Wall/membrane junction.

