

SEALED ACCESS PANEL WATER/AIR/DUST/SMOKE



- Aluminium profile frame secured by «Tox» connections
- Double-sided EPDM seal along the whole circumference
- Safety catch on both sides
- Hidden latches
- GKBI plaster panel
- Fitting instructions and template
- Can be tiled



SIZES AND REFERENCES		12,5 mm Board	
DIMENSIONS IN MM	INTERNAL DIMENSIONS LENGTH x WIDHT	WEIGHT IN KG	REFERENCE
300 x 300	240 x 240	1.9	A04539
400 x 400	340 x 340	2.8	A04540
500 x 500	440 x 440	4	A04541
600 x 600	540 x 540	5.1	A04542
600 x 800	540 x 740	6.7	A04543

Non-stocked items – 3/4 weeks delivery lead time.



SIZES AND	REFERENCES	12,5 mr	n 2 Boards
DIMENSIONS IN MM	INTERNAL DIMENSIONS LENGTH x WIDHT	WEIGHT IN KG	REFERENCE
300 x 300	240 x 240	2.7	A04544
400 x 400	340 x 340	5.7	A04545
500 x 500	440 x 440	6.6	A04546
600 x 600	540 x 540	8.4	A04547
600 x 800	540 x 740	11.3	A04548

Non-stocked items - 3/4 weeks delivery lead time.

PARTICULARITIES OF APPLICATION

- Fit to wall or ceiling (do not walk on it).
- Water permeability tested according to EN 1027 standards: 2000-06 and EN 12208: 1999-11; Report No. 104 32588.
- Smoke tightness tested according to DIN EN 1634-3 standards: 2005-3.
- Air permeability tested according to EN 1026 standards: 2000-09 and EN 12207: 1999-11; Report No. 104 31394/1 and 104 31394/4.
- Water-tightness report: No. 14-002774-PR01.
- Suitable for wet rooms.

QUALITY ASSURANCE

Production quality control is integrated into the manufacturing process of each item. The raw materials and external components undergo the quality control system on arrival of the goods.

MATERIALS

Parts of the frame	Bar profiles, quality Eloxale ALMgSi 0.5 F22
Stopping angle, Stopping device, Angle section, Mounting sheet	Sheet steel, galvanised DC 01 Am 1.5 mm
Spacer sheet, drill template	Sheet steel, galvanised DX51D/Z275 1.00 mm
Plaster board	Board
Latch	Steel/plastic
Seal	EPDM lip seal
Quick mounting screws	Steel



