



#### PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

101 Z275 TRACK / U-type profiles. Structure for wide ceiling heavy gauge profiles.

Available lengths (m)	3
Nominal thickness	6/10 <sup>th</sup>
Protection	Z275
Steel	DX51

## ] ADVANTAGES

 Important resistance and strength of the structure, Z275 protection, especially fast installation.

### ] AREA OF APPLICATION

Structure for ceiling requiring long lengths and/or a high protection against moisture. Resistance to saline mist 190 H.

# 1 REFERENCES TO TECHNICAL **DOCUMENTS**

NF EN 14195 • NF CSTB EOM/88

## INSTRUCTIONS FOR USE

- Fixed horizontally to opposite walls, used to place and fix at 1.20 m intervals primary frames at the ends of the structures
- · After marking, the Tracks 101 are laid and mechanically attached at 0.60 m intervals to the vertical walls parallel to the primary profiles.
- The choice of the fastening methods to the support structures depends on their nature.

#### ] REFERENCES & PACKAGINGS

Lengths/pack Packs/pallet 10 A06298 101 Z275 TRACK L 3.00 28

### DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS?

- 100-45 I HEAVY GAUGE FURRING 21 Z275 Track Interval of 500 and 600

  - F45 6/10th Z275 Furring
- M6 Z275 Hanger
- Z275 Short Coupling

**01 Z275 TRACK**