



] PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

100 - 45 Z275 SHORT COUPLING

Connecting accessories, for connection and mechanical continuity between frames constituting the primary framework. The short coupling consists of two identical parts that fit together and form a shell around the primary profiles.

Product dimensions	Height (in mm)	100
	Width (in mm)	47
	Length (in mm)	90
	Weight (in kg)	0.214
Nominal thickness		10/10 th
Protection		Z275
Steel		DX51

] ADVANTAGES

- Important resistance and strength of the structure, Z275 protection, especially fast installation.

] AREA OF APPLICATION

Structure for ceiling requiring long lengths and/or a high protection against moisture. Resistance to saline mist 190 H.

] INSTRUCTIONS FOR USE

Connection is carried out preferably on the ground and are shifted from on line of the framework to the other.

After centring the coupling on the line joining the profiles. (see sketch of the technical specifications on www.semin.com)

The pre drilled holes (3mm diameter) receive the fixing screws (13mm bugle head self tapping) ensure the mechanical strength of the assembly.

] REFERENCES & PACKAGINGS

A06303	100 - 45 Z275 SHORT COUPLING	Lengths/pack 50	packs /pallet 36
--------	------------------------------	--------------------	---------------------

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- 100-45 I HEAVY GAUGE FURRING Interval of 500 and 600
- 21 Z275 Track
101 Z275 Track
- F45 6/10 th Z275 Furring
- M6 Z275 Hanger